

**High Range, Field Adjustable
Titanium/Silicon-on-Sapphire
PRESSURE SENSOR**

**P600FA
Series**



- **Pressure Ranges 0-1000bar up to 0-2500bar**
- **Vented Gauge**
- **Sealed to IP65**
- **Excellent Chemical and Abrasion Resistance**
- **Rugged Construction**
- **Wide Choice of Electrical Outputs**
- **Field Adjustable output range**
- **Excellent Performance/Price Ratio**
- **3 YEAR WARRANTY**

Options Available

Interim Pressure Ranges (Consult Factory)

Special Output Scaling (Consult Factory)

Supplied With Any Instrumentation and Calibrated as a Complete System with Traceable Certificate

ATEX Certified Version: II I GD EEX ia IIC T4

DESCRIPTION

The P600FA series of pressure sensors has been engineered for the measurement of high range liquid and gas pressures in a diverse range of industrial and specialised applications, including:- Hydraulics, Agriculture, Marine, Gas, Chemical, etc.

Pressure ranges between 1000bar and 2500bar are available offering field adjustment of both span and zero for quick and easy re-ranging of the sensor.

Constructed from Titanium using Silicon on Sapphire technology it offers excellent long term performance throughout the complete range of pressures.

The P600FA series can be further complimented by any of our range of instrumentation to offer a complete system, supplied and calibrated from a single supplier.

Transducer Specialists...

APPLIED MEASUREMENTS LIMITED

3 MERCURY HOUSE - CALLEVA PARK - ALDERMASTON - BERKSHIRE - RG7 8PN - UK

Tel: (+44) 0118 981 7339 Fax: (+44) 0118 981 9121 email: info@appmeas.co.uk Internet: www.appmeas.co.uk



SPECIFICATION

CHARACTERISTICS	P610FA	P605FA	P6010FA	P642FA	UNITS
Pressure Ranges:	0-1000, 0-1500, 0-2000, 0-2500				bar
Rated Output:	10mV/V	0-5V	0-10V	4-20mA	
Excitation Voltage:	5-15 (regulated)	13 to 36 (un-regulated)			Vdc
Input Current:	0.6mA/V	13		N/A	mA
Output Configuration (No. of Wires):	4	3 or 4		2	
Combined Error (Accuracy):	< ±0.25				±% of Rated Output
Zero Balance:	< 1.0				±% of Rated Output
Safe Overpressure:	150 (3000bar max over-pressure on 2000 & 2500bar ranges)				% of Pressure Range
Temperature Range Compensated:	-40 to +85				°C
Operating:	-50 to +125				°C
Temperature Effect On Span:	< 0.02 typical				±% of Output/°C
On Zero:	< 0.02 typical				±% of Rated Output/°C
Stability:	< 0.2 over 6 months				±% of Rated Output
Input Resistance:	1500 ±30%	N/A			ohms
Output Resistance:	1500 ±30%	N/A			ohms
Insulation Resistance:	> 100				Megaohms at 500VDC
Media Compatibility:	Any media compatible with BT9 Titanium Alloy				
Weight:	125 nominal				grams
Environmental Protection:	IP65				

**Combined Error (Accuracy) is the combined error caused by the effects of Non-Linearity, Hysteresis and Repeatability

All dimensions in mm

